



単位: mm

型番	対応冷媒	銅管			保温材		部材数量																																						
		外径	肉厚	L	外径	肉厚	非粘着テープ	粘着テープ	スリーブ	ウォールカバー	パテ	片サドル	ビス	2層式ドレンホース(長さ)	VVF(長さ)																														
							50mm×18m	19mm×5m	TS-64200	UWC-64	HGP-200	KS-1	φ4×30	φ14	2.0mm 3C																														
HS23-30FL-K	2種	6.35	0.8	3,000	24	8	1	1	1	1	4	4	1	1																															
		9.52			27								(3,000)	(4,450)																															
HS23-35FL-K		6.35		3,500	24								2	2	1	1	1	4	4	1	1																								
		9.52			27															(3,500)	(4,950)																								
HS23-40FL-K		6.35		4,000	24															1	1	1	1	4	4	1	1																		
		9.52			27																					(4,000)	(5,450)																		
HS23-50FL-K		6.35		5,000	24																					1	1	1	1	4	4	1	1												
		9.52			27																											(5,000)	(6,450)												
HS23-60FL-K		6.35		6,000	24																											1	1	1	1	4	4	1	1						
		9.52			27																																	(6,000)	(7,450)						
HS23-70FL-K		6.35		7,000	24																																	1	1	1	1	4	4	1	1
		9.52			27																																							(7,000)	(8,450)

④	フレアキャップ	ポリエチレン	ナチュラル	4		日付	2022.04.01	型番	HS23-30FL-K・HS23-35FL-K HS23-40FL-K・HS23-50FL-K HS23-60FL-K・HS23-70FL-K	型名	配管セット 2分3分(フルセット)
③	フレアナット	銅合金	—	4	JIS H 3250 C3771BD 相当	尺度	Free				
②	保温材	ポリエチレン	ホワイト(表皮)	2	JIS A 9511A-PE-C-2 準拠	単位	mm				
①	銅管	りん脱酸銅	—	2	JIS H 3300 C1220T-O	第三角法					
番号	名称	材質	色調	数量	備考	KANTO 関東器材工業株式会社					